




TECHNICAL SPECIFICATION

LEAF TYPE	Leaf Thickness	66mm
	Leaf Surface Material	Galvanize
	Surface Finish	Powder Coated
	Leaf Sheet Thickness	Standard: 0,8mm, Optional: 1,0mm
	Core Type	12,5mm Fire Gypsum, 90 kg/m ³ x 40mm Rockwool, 12,5mm Fire Gypsum
	Reinforcement	Standard: Hinge Reinforcement, Optional: Stiffener
	Rebate on Leaf	Yes / 3mm

FRAME TYPE	Frame Type	Standard: 4 Side Corner Frame, Optional: 3 Side Corner Frame & Block Frame
	Frame Material	Galvanize
	Material Thickness	Standard: 1,5mm, Optional: 1,8mm
	Architrave	60mm
	Surface Finish	Powder Coated
	Rebate On Frame	N/A

DIMENSIONS	Standard Wall Width	500mm
	Standard Wall Height	1000mm
	Standard Wall Thickness	Any
	Min - Max Wall Width	300mm – 900mm
	Min - Max Wall Height	400mm – 2000mm
	Min - Max Wall Thickness	Any

OTHER FEATURES	Hardwares	Optional
	Glazing	N/A
	Louver	Optional by 3rd Party report
	Gasketing	Frame Gasket & Intumescent Gasket
	Acoustical	N/A
	Fire Rating	EI120
	Smoke Proof	N/A
	Certification	AB-0001-T 536742 07-20
	Transom Panel	N/A