




TECHNICAL SPECIFICATION

LEAF TYPE	Leaf Thickness	52mm
	Leaf Surface Material	Galvanize
	Surface Finish	Powder Coated
	Leaf Sheet Thickness	Standard: 1,0mm, Optional: 1,2mm
	Core Type	50 kg/m ³ x 50mm Rockwool
	Reinforcement	Standard: Hinge Reinforcement, Optional: Stiffener
	Rebate on Leaf	Standard: Yes / 3mm, Optional: Non-rebated

FRAME TYPE	Frame Type	Standard: Corner Frame, Optional: Full Frame & Block Frame
	Frame Material	Galvanize
	Material Thickness	Standard: 1,5mm, Optional: 1,8mm
	Architrave	60mm - 72mm
	Surface Finish	Powder Coated
	Rebate On Frame	N/A

DIMENSIONS	Standard Wall Width	1000mm
	Standard Wall Height	2100mm
	Standard Wall Thickness	200mm
	Min - Max Wall Width	400 - 3500mm
	Min - Max Wall Height	400 - 4000mm
	Min - Max Wall Thickness	100 - 390mm

OTHER FEATURES	Hardwares	Optional
	Glazing	Optional
	Louver	Optional
	Gasketing	Frame Gasket
	Acoustical	N/A
	Fire Rating	NFR
	Smoke Proof	N/A
	Certification	KY-28765 / ICA 9001
	Transom Panel	Optional