




TECHNICAL SPECIFICATION

LEAF TYPE	Leaf Thickness	63mm
	Leaf Surface Material	Galvanize
	Surface Finish	Powder Coated
	Leaf Sheet Thickness	Standard: 1,0mm, Optional: 1,2 / 1,5mm
	Core Type	12,5mm Fire Gypsum, 90 kg/m³x 50mm Rockwool
	Reinforcement	Standard: Hinge Reinforcement, Optional: Stiffener
	Rebate on Leaf	Yes / 3mm

FRAME TYPE	Frame Type	Standard: Corner Frame, Optional: Full Frame & Block Frame
	Frame Material	Galvanize
	Material Thickness	Standard: 1,5mm, Optional: 1,8 / 2,0mm
	Architrave	60mm - 72mm
	Surface Finish	Powder Coated
	Rebate On Frame	N/A

DIMENSIONS	Standard Wall Width	1000mm
	Standard Wall Height	2100mm
	Standard Wall Thickness	200mm
	Min - Max Wall Width	400 - 3500mm
	Min - Max Wall Height	400 - 4000mm
	Min - Max Wall Thickness	100 - 390mm

OTHER FEATURES	Hardwares	Standard: Bottom Giotine, Optional: Others
	Glazing	Optional
	Louver	N/A
	Gasketing	Special Frame Gasket + Bottom Giotine
	Acoustical	35dB
	Fire Rating	Up to 120min.
	Smoke Proof	Optional
	Certification	AB-0001-T / 358348
	Transom Panel	N/A