




TECHNICAL SPECIFICATION

LEAF TYPE	Leaf Thickness	42-60mm
	Surface Finish	HPL (High Pressure Laminate), Lacquered, Natural Wood Veneered
	Edge	0.8mm PVC, Lacquered or Veneered
	Facing	Standard: 6mm MDF Optional: 4-8-10-12mm MDF, Plywood or Green MDF for Water Resistance
	Core Type	Standard : Honeycomb Kraft Core Optional : Tubular Chipboard Core
	Rails & Stiles	Standard : Softwood 42mm Optional : Rails can be 2 layer and Stiles can be hardwood
	Lipping	N/A
	Groove	Optional
	Molding	Optional
	Rebate on Leaf	N/A

FRAME TYPE	Frame Material	Standard: MDF Optional: Hardwood
	Material Thickness	Standard: 36mm Optional: 42mm
	Architrave	Standard: 8x80mm MDF Optional: 12x80mm / 18x80mm / 18x100mm
	Surface Finish	CPL, Lacquered, Natural Wood Veneered
	Rebate On Frame	N/A

DIMENSIONS	Standard Wall Width	Single: 800 / 900 / 1000mm Double: 1400 / 1600 / 1800mm
	Standard Wall Height	2100 / 2200mm
	Standard Wall Thickness	110 150 170 210mm
	Max Wall Width	Single: 1300mm Double: 2600mm
	Max Wall Height	Single: 3000mm Double: 3000mm
	Max Wall Thickness	240mm Over 240mm two pcs. frame to be applied
	Doorset Option	Single & Double

OTHER FEATURES	Hardwares	Optional (Surface mounted sliding door mechanism)
	For Glazing	Optional
	For Louver	Optional
	Gasketing	PVC
	Acoustical	N/A
	Fire Rating	N/A
	Certification	ISO 9001 - ISO 14001
	Transom Panel	N/A